

RENDIMIENTO DEL POLIMERO POR M2

M2	Ton a Resistir	Profund. Mts	DOSIS PARA LA BASE	
			Dosis AGB x M3	Requerido Para la Base
1	20	0.10	4	0.40
1	40	0.15	4	0.60
1	80	0.20	4	0.80
1	200	0.25	4	1.00
1	700	0.30	4	1.20

DOSIS PARA SELLAR LA BASE		
Con 1 Sello	Con 2 Sellos	Con 3 Sellos
0.25	0.50	0.75
0.25	0.50	0.75
0.25	0.50	0.75
0.25	0.50	0.75
0.25	0.50	0.75

RENDIMIENTO DE UN (1) TOTE DE 1,000 LITROS

TOTE - Lts	PARA LA BASE			PARA EL SELLADO		
	Ton a Resistir	Requerido Para la Base	M2 A FABRICAR	M2 A SELLAR - 1 Sello	M2 A SELLAR - 2 Sellos	M2 A SELLAR - 3 Sellos
1,000	20	0.40	2,500	4,000	2,000	1,334
1,000	40	0.60	1,667	4,000	2,000	1,334
1,000	80	0.80	1,250	4,000	2,000	1,334
1,000	200	1.00	1,000	4,000	2,000	1,334
1,000	700	1.20	834	4,000	2,000	1,334